


































Flat cables		
 #01829 Net Price: 8,65 EUR Unit: roll 100m Flat cable, 2C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	 #00819 Net Price: 8,65 EUR Unit: roll 100m Flat cable, 2C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	 #04917 Net Price: 6,69 EUR Unit: roll 100m Flat cable, 4C, 10/6, black, 100 m/R CCS Wire: CCS 6x0.1mm Length: 100m
 #04916 Net Price: 6,69 EUR Unit: roll 100m Flat cable, 4C, 10/6, white, 100 m/R CCS Wire: CCS 6x0.1mm Length: 100m	 #01808 Net Price: 12,00 EUR Unit: roll 100m Flat cable, 4C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	 #04808 Net Price: 36,00 EUR Unit: roll 300m Flat cable, 4C, 12/7, black, 300 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 300m
 #04001 Net Price: 12,00 EUR Unit: roll 100m Flat cable, 4C, 12/7, grey, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	 #00820 Net Price: 12,00 EUR Unit: roll 100m Flat cable, 4C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	 #04807 Net Price: 36,00 EUR Unit: roll 300m Flat cable, 4C, 12/7, white, 300 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 300m
 #01810 Net Price: 18,90 EUR Unit: roll 100m Flat cable, 6C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	 #00822 Net Price: 18,90 EUR Unit: roll 100m Flat cable, 6C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	 #01812 Net Price: 24,10 EUR Unit: roll 100m Flat cable, 8C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m
 #00823 Net Price: 24,10 EUR Unit: roll 100m Flat cable, 8C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m		

Handset and extension cords		
 <p>#01819 Net Price: 0,532 EUR Unit: pcs</p> <p>Handset cord, 15ft, black Spiral connection cords are made of flat wire 7x0,12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.</p>	 <p>#00855 Net Price: 0,532 EUR Unit: pcs</p> <p>Handset cord, 15ft, white Spiral connection cords are made of flat wire 7x0,12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.</p>	 <p>#01830 Net Price: 0,375 EUR Unit: pcs</p> <p>Handset cord, 7ft, black Spiral connection cord SP1 (terminated with two 4p4c modular plugs). Spiral connection cords are made of flat wire 7x0,12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.</p>
 <p>#00851 Net Price: 0,375 EUR Unit: pcs</p> <p>Handset cord, 7ft, white Spiral connection cord SP1 (terminated with two 4p4c modular plugs). Spiral connection cords are made of flat wire 7x0,12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.</p>	 <p>#01817 Net Price: 0,859 EUR Unit: pcs</p> <p>Handset cord, tinsel, 12ft, black Spiral tinsel cords are used for interconnecting moving parts (i.e. handsets) of telecommunication indoor devices (i.e. desktop phones). Cord is made from flat, 4-wires cable strenghtened with tetron braid. High quality manufacturing and durability (can stand 100 thousand inflexions) make SP1..S cords very popular among installers and manufacturers.</p>	 <p>#00854 Net Price: 0,920 EUR Unit: pcs</p> <p>Handset cord, tinsel, 12ft, white Spiral tinsel cords are used for interconnecting moving parts (i.e. handsets) of telecommunication indoor devices (i.e. desktop phones). Cord is made from flat, 4-wires cable strenghtened with tetron braid. High quality manufacturing and durability (can stand 100 thousand inflexions) make SP1..S cords very popular among installers and manufacturers.</p>
 <p>#01815 Net Price: 0,695 EUR Unit: pcs</p> <p>Handset cord, tinsel, 7ft, black Spiral tinsel cords are used for interconnecting moving parts (i.e. handsets) of telecommunication indoor devices (i.e. desktop phones). Cord is made from flat, 4-wires cable strenghtened with tetron braid. High quality manufacturing and durability (can stand 100 thousand inflexions) make SP1..S cords very popular among installers and manufacturers.</p>		
LSA installation equipment		
 <p>#01901 Net Price: 1,31 EUR Unit: pcs</p> <p>10 pairs connection module, number 0-9, grey LSA terminal blocks consist of two rows of contacts, one for the permanent plowing of the cable and the other for the crossing.</p>	 <p>#01884 Net Price: 1,31 EUR Unit: pcs</p> <p>10 pairs connection module. Base: grey, Housing: grey LSA terminal blocks consist of two rows of contacts, one for the permanent plowing of the cable and the other for the crossing. Crimping tools: #01889 - Punch down tool, krone type terminal (Hanlong HT-314KR) #02303 - (CT-314KR) Punch down tool, Krone type terminal #04284 - Punch down tool, 110/88 terminal (Hanlong HT-364BR) #04283 - Punch down tool, 110/88+krone type terminal (Hanlong HT-344KR) #04795 - Punch down tool, krone type terminal Chosen panel mounts and distribution boxes: #04914 - Panel mount 19" 1U #04906 - Mounting frame for 10 pairs module, 41 ways, dividable</p>	 <p>#01900 Net Price: 1,31 EUR Unit: pcs</p> <p>10 pairs disconnect module, number 0-9, white 10 pairs connection/disconnection module. Enables testing each line separately and mounting lighting protectors.</p>



 <p>#01873 Net Price: 1,31 EUR Unit: pcs</p> <p>10 pairs disconnection module. Base: grey, Housing: white</p> <p>LSA terminal blocks consist of two rows of contacts, one for the permanent plowing of the cable and the other for the crossing.</p> <p>Crimping tools: #01889 - Punch down tool, krone type terminal (Hanlong HT-314KR) #02303 - (CT-314KR) Punch down tool, Krone type terminal #04284 - Punch down tool, 110/88 terminal (Hanlong HT-364BR) #04283 - Punch down tool, 110/88+krone type terminal (Hanlong HT-344KR) #04795 - Punch down tool, krone type terminal</p> <p>Chosen panel mounts and distribution boxes:</p> <p>#04914 - Panel mount 19" 1U #04906 - Mounting frame for 10 pairs module, 41 ways, dividable</p>	 <p>#07816 Net Price: 0,440 EUR Unit: pcs</p> <p>Mounting frame 1x10 pairs module</p>	 <p>#04753 Net Price: 1,43 EUR Unit: pcs</p> <p>Mounting frame for 10 pairs module, 3 ways</p>
 <p>#01902 Net Price: 2,25 EUR Unit: pcs</p> <p>Mounting frame for 10 pairs module, 5 ways</p>	 <p>#04752 Net Price: 4,50 EUR Unit: pcs</p> <p>Mounting frame for 10 pairs module, 10 ways</p>	 <p>#04906 Net Price: 20,70 EUR Unit: pcs</p> <p>Mounting frame for 10 pairs module, 41 ways, dividable</p> <p>Allows separating (by breaking off) any required number of mounting brackets.</p> <p>Material: stainless steel sheet, 0.75 mm thick Lacquer cladding: no</p>
 <p>#04914 Net Price: 8,14 EUR Unit: pcs</p> <p>Panel mount 19" 1U , 60 ways</p> <p>The panels of telephone connectors are made of stainless steel. They have appropriate profiling allowing for "push-fit" mounting of all types of telephone connectors.</p> <p>Width: 483mm Height: 44mm Depth: 81mm Weight: 0.30kg Material: stainless steel sheet, 0.75mm thick Lacquer cladding: no</p>	 <p>#07409 Net Price: 13,90 EUR Unit: pcs</p> <p>Panel mount 19" 3U, 150 ways</p> <p>The panels of telephone connectors are made of stainless steel. They have appropriate profiling allowing for "push-fit" mounting of all types of telephone connectors.</p> <p>Width: 483mm Height: 133mm Depth: 70mm Weight: 0.60kg Material: stainless steel sheet, 1.00mm thick, plastic cable holders</p>	 <p>#03810 Net Price: 12,30 EUR Unit: pcs</p> <p>Panel mount 19" 3U, 150 ways, black</p> <p>The panels of telephone connectors are made of stainless steel. They have appropriate profiling allowing for "push-fit" mounting of all types of telephone connectors.</p>
 <p>#07447 Net Price: 6,25 EUR Unit: pcs</p> <p>Distribution box, 10 pairs, outdoor</p> <p>Water and dust resistance: compliant with IP 54. The height of the box enables installation in the terminal box together with the lightning arrester magazine #01885</p> <p>Water and dust resistance: compliant with IP 54 Dimensions: 19x11.5x9 cm</p>	 <p>#01896 Net Price: 2,86 EUR Unit: pcs</p> <p>Distribution box, 30 pairs, indoor</p> <p>Height: 55mm Width: 100mm Length: 150mm</p>	 <p>#07449 Net Price: 7,91 EUR Unit: pcs</p> <p>Distribution box, 30 pairs, indoor</p> <p>Height: 92mm Width: 175mm Length: 165mm</p>
 <p>#04787 Net Price: 8,57 EUR Unit: pcs</p> <p>Distribution box, 30 pairs, outdoor</p> <p>Water and dust resistance: compliant with IP 54</p>	 <p>#01897 Net Price: 9,80 EUR Unit: pcs</p> <p>Distribution box, 50 pairs, indoor</p> <p>Height: 105mm Width: 200mm Length: 185mm</p>	 <p>#04788 Net Price: 11,60 EUR Unit: pcs</p> <p>Distribution box, 50 pairs, outdoor</p> <p>Water and dust resistance: compliant with IP 54 Dimensions: 195x195x85mm</p>

 <p>#01898 Net Price: 14,40 EUR Unit: pcs</p> <p>Distribution box, 100 pairs, indoor Height: 105mm Width: 200mm Length: 370mm</p>	 <p>#04789 Net Price: 7,95 EUR Unit: pcs</p> <p>Distribution box, 100 pairs, outdoor Water and dust resistance: compliant with IP 54 Outer dimensions: 190x370x110mm (whd)</p>	 <p>#08345 Net Price: 41,80 EUR Unit: pcs</p> <p>Distribution box, 300 pairs, indoor Dimensions: 420x450x76mm (width x height x depth)</p>
 <p>#07483 Net Price: 48,40 EUR Unit: pcs</p> <p>Distribution box, 300 pairs, indoor, metal Distribution box designed for wall mounting, enabling the installation of 30 10-way connectors Material: steel, 0.9mm Closing method: key-locked Dimensions: 600x450x130mm (width x height x depth)</p>	 <p>#07484 Net Price: 152,00 EUR Unit: pcs</p> <p>Distribution box, 1000 pairs, indoor, metal Dimensions: 700x1000x130mm (width x height x depth)</p>	 <p>#04775 Net Price: 0,323 EUR Unit: pcs</p> <p>2 pole test male connector</p>
 <p>#04776 Net Price: 0,532 EUR Unit: pcs</p> <p>4 pole test male connector</p>	 <p>#04777 Net Price: 1,10 EUR Unit: pcs</p> <p>Test cable with alligator clip 2 pole, 1.5m</p>	 <p>#04778 Net Price: 1,39 EUR Unit: pcs</p> <p>Test cable with alligator clip 4 pole, 1.5m</p>
 <p>#01892 Net Price: 0,798 EUR Unit: pcs</p> <p>Test cord, 2P with modular 6P2C, 2 m For use with disconnection modules.</p>	 <p>#01893 Net Price: 1,27 EUR Unit: pcs</p> <p>Test cord, 4P with modular 6P4C, 2 m For use with disconnect modules.</p>	 <p>#01885 Net Price: 1,94 EUR Unit: pcs</p> <p>10 pairs 3-pole surge arrester magazine</p>
 <p>#01888 Net Price: 0,020 EUR Unit: pcs</p> <p>Disconnection male connector</p>	 <p>#01895 Net Price: 0,564 EUR Unit: pcs</p> <p>Gas tube surge arrester, 3-pole, fail safe 3 Pole Gas Arrester protects telecommunication circuits against overvoltage which are usually caused by lightning. Arresters are placed individually in special magazines, for each contact separately. Resistance grounding system should not exceed 4 ohms, which will provide the most effective protection when connected to the 3 pole gas arresters. Size: 8x10mm Voltage: 230V Maximum impulse spark-over voltage: 800V (1KV/μs) Impulse discharge current: 10kA, 8/20μs; 10 times Impulse discharge current: 100A, 10/100μs; 300 times</p>	 <p>#04762 Net Price: 0,286 EUR Unit: pcs</p> <p>Hinged label holder for 10 pairs</p>
 <p>#01890 Net Price: 0,225 EUR Unit: pcs</p> <p>Label holder for mounting frame</p>	 <p>#01905 Net Price: 0,164 EUR Unit: pcs</p> <p>Numbering kits 0-9</p>	 <p>#01906 Net Price: 0,164 EUR Unit: pcs</p> <p>Numbering kits 10-100</p>

Modular connectors, male		
 <p>#00876 Net Price: 1,57 EUR Unit: 100pcs</p> <p>Modular male connector, 4P4C (RJ-10), 100/bag Modular male connectors are used for terminating wires in phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold 3µm). Connector, contacts: RJ-10, 4p4c Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: flat, stranded Connector type: unshielded</p>	 <p>#00877 Net Price: 1,53 EUR Unit: 100pcs</p> <p>Modular male connector, 6P2C, 100/bag Modular male connectors are used for terminating wires in phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold 3µm). Type, contacts: 6p2c Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: flat, stranded Connector type: unshielded</p>	 <p>#00878 Net Price: 1,80 EUR Unit: 100pcs</p> <p>Modular male connector, 6P4C (RJ-11), 100/bag Modular male connectors are used for terminating wires in phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold 3µm). Type, contacts: RJ-11, 6p4c Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: flat, stranded Connector type: unshielded</p>
 <p>#00879 Net Price: 2,25 EUR Unit: 100pcs</p> <p>Modular male connector, 6P6C (RJ-12), 100/bag Modular male connectors are used for terminating wires in phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold 3µm). Type, contacts: RJ-12, 6p6c Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: flat, stranded Connector type: unshielded</p>	 <p>#04794 Net Price: 9,41 EUR Unit: 100pcs</p> <p>Modular male connector, 8P8C (RJ-45), round, shielded, cat. 5e, throughconnector (EZ type) Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-45, 8p8c Category: 5e Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: shielded, EZ type</p>	 <p>#04975 Net Price: 10,20 EUR Unit: 100pcs</p> <p>Modular male connector, 8P8C (RJ-45), round, shielded, cat. 6A, throughconnector (EZ type) Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-45, 8p8c Category: 6A Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: shielded, EZ type</p>
 <p>#04196 Net Price: 4,77 EUR Unit: 100pcs</p> <p>Modular male connector, 8P8C (RJ-45), round, cat. 5e, throughconnector (EZ type) Type, contacts: RJ-45, 8p8c Category: 5e Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: unshielded, EZ type</p>	 <p>#04195 Net Price: 6,00 EUR Unit: 100pcs</p> <p>Modular male connector, 8P8C (RJ-45), round, cat. 6, throughconnector (EZ type) Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-45, 8p8c Category: 6 Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: unshielded, EZ type</p>	 <p>#04197 Net Price: 6,55 EUR Unit: 100pcs</p> <p>Modular male connector, 8P8C (RJ-45), round, cat. 6A, throughconnector (EZ type) Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-45, 8p8c Category: 6A Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: unshielded, EZ type</p>
 <p>#04955 Net Price: 0,932 EUR Unit: pcs</p> <p>Modular male connector, 8P8C (RJ-45), cat. 5e, toolless Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-45, 8p8c Category: 5e Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: unshielded, toolless</p>	 <p>#03834 Net Price: 2,00 EUR Unit: pcs</p> <p>Modular male connector, 8P8C (RJ-45), cat. 6, shielded, toolless Modular male connectors are used for terminating wires in phone or computer installations. Shielded - for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-45, 8p8c Category: 6 Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: shielded, toolless</p>	 <p>#04956 Net Price: 1,02 EUR Unit: pcs</p> <p>Modular male connector, 8P8C (RJ-45), cat. 6, toolless Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-45, 8p8c Category: 6 Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: unshielded, toolless</p>


#03835

Net Price:
2,59 EUR
Unit: pcs

Modular male connector, 8P8C (RJ-45), cat. 6A, shielded, toolless

Modular male connectors are used for terminating wires in phone or computer installations. Shielded - for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 6a

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, solid and stranded

Connector type: shielded, toolless


#00882

Net Price:
3,58 EUR
Unit: 100pcs

Modular male connector, 8P8C (RJ-45), flat, solid, cat. 5e

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 5e

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: flat, solid

Connector type: unshielded


#00880

Net Price:
3,68 EUR
Unit: 100pcs

Modular male connector, 8P8C (RJ-45), flat, stranded, cat. 5e

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 5e

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: flat, stranded

Connector type: unshielded


#00883

Net Price:
3,78 EUR
Unit: 100pcs

Modular male connector, 8P8C (RJ-45), round, solid, cat. 5e

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 5e

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, solid

Connector type: unshielded


#00884

Net Price:
0,094 EUR
Unit: pcs

Modular male connector, 8P8C (RJ-45), round, solid, cat. 5e, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 5e

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, solid

Connector type: shielded


#04912

Net Price:
0,092 EUR
Unit: pcs

Modular male connector, 8P8C (RJ-45), round, solid, cat. 6

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 6

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, solid

Connector type: unshielded


#04913

Net Price:
0,133 EUR
Unit: pcs

Modular male connector, 8P8C (RJ-45), round, solid, cat. 6, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type of - for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 6

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, solid

Connector type: shielded


#07165

Net Price:
0,200 EUR
Unit: pcs

Modular male connector, 8P8C (RJ-45), round, solid, cat. 6A, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 6A

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, solid

Connector type: shielded

Maximum core diameter: 1.02mm

Operating temperature: -40° ÷ 125°C


#00881

Net Price:
3,68 EUR
Unit: 100pcs

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 5e

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 5e

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, stranded

Connector type: unshielded


#00897

Net Price:
0,104 EUR
Unit: pcs

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 5e, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 5e

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, stranded

Connector type: shielded


#04919

Net Price:
0,035 EUR
Unit: pcs

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 5e, short body

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 5e

Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, stranded

Connector type: unshielded, short-body


#07408

Net Price:
0,123 EUR
Unit: pcs

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 6, shielded

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 6

















Materials: polycarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au

Cable type: round, stranded

Connector type: shielded

 <p>#04902 Net Price: 0,109 EUR Unit: pcs</p> <p>Modular male connector, 8P8C (RJ-45), round, stranded, cat. 6, w/insert bar Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-45, 8p8c Category: 6 Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: unshielded</p>	 <p>#07166 Net Price: 0,200 EUR Unit: pcs</p> <p>Modular male connector, 8P8C (RJ-45), round, stranded, cat. 6A, shielded Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-45, 8p8c Category: 6A Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: shielded</p>	 <p>#07184 Net Price: 0,245 EUR Unit: pcs</p> <p>Modular male connector, 8P8C (RJ-45), round, cat. 8, shielded High quality plugs designed for cat. 8 applications. New 3 pongs contacts are suitable for both solid and stranded wires. Type, contacts: RJ-45, 8p8c Category: 8 Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: shielded Maximum core diameter: 1.45mm Operating temperature: -40° + 125°C Outer cable OD max: 8mm</p>
 <p>#00895 Net Price: 0,053 EUR Unit: pcs</p> <p>Modular male connector, 10P10C (RJ-50), round, solid The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-50, 10p10c Category: n/a Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid Connector type: unshielded</p>	 <p>#00896 Net Price: 0,053 EUR Unit: pcs</p> <p>Modular male connector, 10P10C (RJ-50), round, stranded The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-50, 10p10c Category: n/a Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: unshielded</p>	 <p>#04796 Net Price: 0,098 EUR Unit: pcs</p> <p>Modular male connector, 10P10C (RJ-50), round, stranded, shielded Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold). Type, contacts: RJ-50, 10p10c Category: n/a Materials: polycarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: shielded</p>
 <p>#04305 Net Price: 0,205 EUR Unit: pcs</p> <p>Swivel male connector WMP 2, anti-torsion, modular</p>	 <p>#00494 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/ear, o.d. 6.0 mm, black</p>	 <p>#00495 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/ear, o.d. 6.0 mm, blue</p>
 <p>#00496 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/ear, o.d. 6.0 mm, green</p>	 <p>#00425 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/ear, o.d. 6.0 mm, grey</p>	 <p>#00497 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/ear, o.d. 6.0 mm, red</p>
 <p>#03751 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/ear, o.d. 6.0 mm, white</p>	 <p>#00498 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/ear, o.d. 6.0 mm, yellow</p>	 <p>#07185 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/ear, o.d. 8.0 mm, grey</p>
 <p>#05124 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/inserts, black</p>	 <p>#05125 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/inserts, blue</p>	 <p>#05126 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/inserts, green</p>

 <p>#05127 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/inserts, grey</p>	 <p>#05128 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/inserts, red</p>	 <p>#05130 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/inserts, white</p>
 <p>#05129 Net Price: 0,020 EUR Unit: pcs</p> <p>Cable boot w/inserts, yellow</p>		
Other devices		
 <p>#00873 Net Price: 5,91 EUR Unit: pcs</p> <p>Bell ringer with light, B type UT-7 device amplifies the phones' ring signal and additionally includes a blinking light, which switches on when the phone is ringing. There is an option of choosing only the blinking light function which is a perfect solution for deaf people. Works with any analogue phone line.</p>		
Phone equipment, polish std.		
 <p>#00816 Net Price: 0,419 EUR Unit: pcs</p> <p>Adaptor, polish male to 2 american female</p>	 <p>#01838 Net Price: 0,177 EUR Unit: pcs</p> <p>Wall plate, polish female & american female</p>	 <p>#00874 Net Price: 0,130 EUR Unit: pcs</p> <p>Connector, polish male</p>
Splitters, couplers		
 <p>#00813 Net Price: 0,225 EUR Unit: pcs</p> <p>Coupler, R1-4, 1F/1F 6p4c</p>	 <p>#00814 Net Price: 0,286 EUR Unit: pcs</p> <p>Coupler, R1-6, 1F/1F 6p6c</p>	 <p>#00815 Net Price: 0,327 EUR Unit: pcs</p> <p>Coupler, R1-8, 1F/1F 8p8c Coupler with two 8p8c sockets for telephone installations use. Couplers meant for computer networks: #06492- Inline coupler, cat 5e, shielded #08317- Inline coupler, cat 5e, shielded, mini #04920- Cat 5e Coupler, UTP</p>
 <p>#00842 Net Price: 0,368 EUR Unit: pcs</p> <p>3 way coupler, 4C, white</p>	 <p>#00843 Net Price: 0,450 EUR Unit: pcs</p> <p>3 way coupler, 6C, white</p>	 <p>#00844 Net Price: 0,430 EUR Unit: pcs</p> <p>3 way coupler, 8C, white</p>
 <p>#00850 Net Price: 1,33 EUR Unit: pcs</p> <p>5 way adaptor, 4C, white</p>	 <p>#00845 Net Price: 0,132 EUR Unit: pcs</p> <p>Duplex adaptor, 4C, white</p>	 <p>#00846 Net Price: 0,430 EUR Unit: pcs</p> <p>Duplex adaptor, 6C, white</p>



#00847
Net Price:
0,511 EUR
Unit: pcs

Duplex adaptor, 8C, white

Surface-mount boxes



#04923
Net Price:
0,327 EUR
Unit: pcs

Surface box, 6P4C, economic, white

Dimensions: 28x42x24 mm



#04927
Net Price:
0,389 EUR
Unit: pcs

Surface box, 6P4C, standard, white

Dimensions: 50x50x21 mm



#04925
Net Price:
0,470 EUR
Unit: pcs

Surface dual box, 2x6P4C, economic, white



#01849
Net Price:
1,02 EUR
Unit: pcs

Wall box, 2x6P4C, ABS, top entry, white



#04924
Net Price:
0,409 EUR
Unit: pcs

Surface box, 6P6C, economic, white



#04921
Net Price:
0,491 EUR
Unit: pcs

Surface box, 6P6C, standard, white



#04922
Net Price:
0,536 EUR
Unit: pcs

Surface box, 8P8C, standard, white

Other phone accessories



#01847
Net Price:
4,34 EUR
Unit: 100pcs

UR connector, 100pcs/bag

UR connectors enable connecting wires without the need of isolation stripping. They are filled with gel, which protects wires from corrosion.

UR connectors should be used for wires with external coat up to 1.67mm in diameter and 0.4-0.9 wire diameter. Made of transparent polycarbonate with a red clamp.

Purpose: connecting three wires
Maximum diameter of the external coat: 1.67mm
Core diameter: 0.4-0.9mm
Dimensions: 19x12x8.5mm (6mm after tightening)
Filling: hydrophobic gel, protecting against corrosion
Packaging: cardboard, 61x63x57mm



#01846
Net Price:
1,47 EUR
Unit: 100pcs

UY connector, 100pcs/bag

UY connectors enable connecting wires without the need of isolation stripping. They are filled with gel, which protects wires from corrosion.

UY connectors should be used for wires with external coat up to 1.52mm in diameter and 0.4-0.7 wire diameter. Made of transparent polycarbonate with a yellow clamp.

Purpose: connecting two wires
Maximum diameter of the external coat: 1.52mm
Core diameter: 0.4-0.7mm
Dimensions: 12x8.5x8mm (6mm after tightening)
Filling: hydrophobic gel, protecting against corrosion
Packaging: cardboard, 55x55x55mm



#04905
Net Price:
2,17 EUR
Unit: 100pcs

UY2 connector, 100pcs/bag

UY2 connectors enable connecting wires without the need of isolation stripping. They are filled with gel, which protects wires from corrosion.

UY2 connectors should be used for wires with external coat up to 1.52mm in diameter and 0.4-0.9 wire diameter. Made of transparent polycarbonate with an orange clamp.

Purpose: connecting two wires
Maximum diameter of the external coat: 1.52mm
Core diameter: 0.4-0.9mm
Dimensions: 15x10x8mm (6mm after tightening)
Filling: hydrophobic gel, protecting against corrosion
Temperature range: -30°C ÷ +70°C
Packaging: cardboard, 55x55x55mm

Index

Flat cables	1
Handset and extension cords	2
LSA installation equipment	2
Modular connectors, male	5
Other devices	8
Phone equipment, polish std.	8
Splitters, couplers	8
Surface-mount boxes	9
Other phone accessories	9